

Product Number: 25129

Order Abbreviation: F96T12/CW/HO/CT/ECO

General Description: 110W, 96" MOL, T12 HO (800 mA) rapid start fluorescent lamp, Cool Whitephosphor, 4200K color temperature, 60 CRI, labeled for cold temperature applications.



*** Full Case Required**

Product Information

| | |
|------------------------------|-----------------------------|
| Abbrev. With Packaging Info. | F96T12CWHOCTECO 15/CS 1/SKU |
| Actual Length (in) | 93.909 |
| Actual Length (mm) | 2385.29 |
| Average Rated Life (hr) | 12000 |
| Base | Recessed Double Contact |
| Bulb | T12 |
| Color Rendering Index (CRI) | 60 |
| Color Temperature/CCT (K) | 4200 |
| Diameter (in) | 1.593 |
| Diameter (mm) | 40.46 |
| Family Brand Name | Ecologic® |
| Initial Lumens at 25C | 8600 |
| Mean Lumens at 35C | 6966 |
| Nominal Length (in) | 96.000 |
| Nominal Length (mm) | 2438.40 |
| Nominal Wattage (W) | 110.00 |



Footnotes

- Approximate initial lumens after 100 hours operation.
- The life ratings of fluorescent lamps are based on 3 hr. operating cycles under specified conditions and with ballast meeting ANSI specifications. If operating cycle is increased, there will be a corresponding increase in the average hours life.
- Minimum starting temperature is a function of the ballast; consult the ballast manufacturer.
- SYLVANIA ECOLOGIC fluorescent lamps are designed to pass the Federal Toxic Characteristic Leaching Procedure (TCLP) criteria for classification as non-hazardous waste in most states. TCLP test results are available upon request. Lamp disposal regulations may vary, check your local & state regulations. For more information, please visit www.lamprecycle.org
- Labeled for cold temperature (below 60 degrees F) operation only per EPACT.*
- Average life rating at 12 hours operation per start is 18,000 hours.
- Mean lumens are measured at 40% of average rated lamp life.
- The distance between any parts of the lamp and any conductive surface of the luminaire should not be less than 3 mm (applies to all high frequency ballasted systems).
- The lamp should not be in contact with any surface of the luminaire (applies to either high frequency or 60Hz ballasted systems).