

TRANSLUCENT FILMS

SPMTUR

4.0 mil. White Semi-Gloss Translucent Calendered Vinyl with Removable Acrylic Ahesive and a 90# Release Liner

Catalina Graphic Films' Mojave Translucent Film is the ideal solution for both photographic and high quality signage applications where vivid color saturation and extreme image resolution is required. This front print glossy backlit film offers maximum color density with the advanced ink adhesion technology, while a higher percentage of translucency achieves excellent color reproduction and saturation.

RECOMMENDED APPLICATIONS		
•	Fleet without Rivets	
•	Backlit	
•	Indoor	
•	Outdoor	

OVERVIEW	
Face Film	3.5 ± 0.2 mils matte white, translucent, polymeric flexible vinyl
Adhesive	R32 Removable Acrylic
Liner	90-lb. (6.5 ± 0.2 mils) white, polyethylene- coated-two-side, silicone-coated-one-side paper
Opacity	Translucent
Gloss Level	Matte
Outdoor Durability	Up to 5 Years
Indoor Durability	Up to 7 Years

SPECIFICATIONS			
Application	Excellent for backlit and internally-illuminated signage & taxi-top applications. Ideal uses include gas station canopies, awnings, blinds, light boxes, shop fascias and other internally illuminated signage or creative and colorful window graphics. Ideally suited for mild solvent and solvent inks.		
Print Methods	Eco-Sol, solvent, UV, and laytex based inkjet systems.		
Total Product Thickness	10.5 – 11.5 mils		
Minimum Application Temperature	+35° F.		
Service Temperature Range	-20° F to +150° F.		
Adhesion	2 - 3 oz. per lineal inch width (180 peel from Stainless Steel; 15-minute, room temperature dwell on test panel).		
Water Resistance	Good.		
Solvent Resistance	Good for most petroleum solvents and lower aliphatic alcohols. For ultimate solvent resistance, edge sealing is recommended.		
Shelf Life	One (1) year when stored under conditions of 70°F and 50% relative humidity.		

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

> To order or request product samples, contact your local authorized dealer or call direct

Customer Service 800 - 333 - 3136 or visit our websites:



27001 Agoura Road Phone: (818) 880-8060 Suite 100 Calabasas Hills California 91301

Fax: (818) 880-1144

Atlanta Sales: (800) 922-5880 Chicago Sales: (800) 766-4939

E-mail: info@catalinagraphicfilms.com



