

1626 Bridgewater Road Bensalem, PA 19020 Toll Free: 800-331-1373

Fax: 215-245-8554 www.prestotape.com

Technical Data Sheet

7186P-LFA High Tack Layflat Application Tape

Product Description:

This is a *premier*, latex saturated application tape with a natural rubber high tack adhesive used for the clean pick-up and transfer of lettering and graphics. The product sticks and lays flat to the exposed release liner and cut vinyl graphics to protect against wrinkling, tunneling and edge curling. 7186P-LFA is recommended for use on computer cut graphics and die-cut lettering and is especially good for use with small and medium size plotters.

Product Properties / Characteristics: Thickness:	Nominal Results 4.0-4.5 mils
PSTC 33	
Adhesion to Steel: PSTC I (oz/in)	17-19
Tack Level:	High
Elongation (%): PSTC 31	3-4
Tear Resistance (grams)	4
Tensile Strength (lb./in.)	40

The values listed above are averages determined by standard production testing procedures. The suitability for use shall be determined by the user for the particular application.

<u>Limitations of Warranty:</u> Presto Tape and seller warrants to customers that coated products constructed and delivered by Presto Tape and seller to be free of defects in workmanship and to meet the specifications published by Presto Tape which are available upon request. for a period of six (6) months from date of delivery and in the event of Presto Tape brand product proved to be defective, the excluding solution, at Presto Tape's option, shall be a) refund the purchase price b) repair or c) replace the defective product. No acceptance or responsibility for loss, or expense, implied or otherwise, shall be assumed by seller or manufacturer. User assumes all risk and liability in connection herewith.

This stated Warranty & Limitation of Liability can only be changed through a written agreement by an authorized officer of Presto Tape.