

▶ DPF 313 Banner (1000D)

Digital Print Scrim PVC Banner

DPF 313 is a frontlit 368,5g white, scrim PVC banner. Available in matte and high gloss, both finishes are smooth and yield high print resolution and image quality. It is a multi-purpose banner suitable for digital printing, screen printing and adhesive-backed vinyl application. DPF 313 is enhanced with 1000 Denier scrim giving the product greater tear and curl resistance. Furthermore, DPF 313 passes the NFPA 701 fire resistant certification test. Use DPF 313 for a wide range of indoor and outdoor banner applications. DPF 313 is rated for outdoor durability up to 1 year (unprinted). Printed durability is dependent on the ink system use.

APPLICATIONS & FEATURES

- Digital printing with a wide variety of direct print systems
- Indoor and outdoor merchandising and display graphics
- Billboard applications
- Shorter-term banner applications

PERFORMANCE & PHYSICAL DATA

| PROPERTY | TYPICAL VALUE |
|--------------------------------|---|
| THICKNESS | 425 microns |
| CONSTRUCTION | 368.5g flexible, polyester scrim banner |
| YARN (DENIER) | 1000 x 1000 Denier |
| THREAD COUNT | 9 x 9 |
| OPACITY | > 95% |
| TENSILE STRENGTH (WARP / WEFT) | 30/33 kgf/cm |
| TEAR STRENGTH (WARP / WEFT) | 10/9 kgf/cm |
| PEEL STRENGTH (WARP / WEFT) | 15.5/15.5 kgf/cm |
| SHELF LIFE | 1 year from factory shipment. (Free from excessive moisture, temperature and direct sunlight) |
| STORAGE TEMPERATURE | 30°C or lower |
| FIRE RESISTANCE | Flammability NFPA 701-2004 Test I |
| PRINTABILITY | Standard solvent and eco-solvent digital inks |

Standard Terms & Conditions Apply

USA

 200 Boysenberry Lane, Placentia, CA 92870
 800 232 7161 / +1 714 985 6300
 +1 714 985 6305

EUROPE

 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
 +31 70 354 4311
 +31 70 355 7721

CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400
 +86 0536 6226568

TERMS & CONDITIONS

The following is made in lieu of all warranties expressed or implied:

All statements, technical information and recommendations published by Arlon relating to Arlon products are based on tests believed to be reliable and within the accuracy of the equipment used to obtain the specific values. Their accuracy or completeness is not guaranteed and Arlon makes no warranty with regard thereto. Seller's and manufacturer's only responsibility shall be to replace any quantity of the product proved defective. Seller and manufacturer shall not be liable for injury, loss or damage, direct or consequential, arising out of use or the inability to use the product. Nor shall seller or manufacturer be liable for any costs or expenses incurred in the processing or printing on the product. Before using, user shall determine the suitability of the product for its intended use. User assumes all risk and liability of every nature in connection therewith. No statements or recommendations other than those contained in the technical information published by Arlon shall have force or effect unless contained in an agreement manually signed by the officers of seller and manufacturer.

April 2020

USA

 200 Boysenberry Lane, Placentia, CA 92870
 800 232 7161 / +1 714 985 6300
 +1 714 985 6305

EUROPE

 Dr. Lelykade 22B, 2583CM Den Haag, The Netherlands
 +31 70 354 4311
 +31 70 355 7721

CHINA

 No. 1989 Xinchang Road, Weifang, Shandong, 262400
 +86 0536 6226568