



## panoRama One8020, 7030, 6040, 5050

A self-adhesive, outside mount, perforated, one-way vision window film for short-term applications.

Ideal for shorter-term applications where quality and economy meet.

Available in 80/20, 70/30, 60/40, and 50/50 film/open ratios.

### APPLICATIONS

- Retail Windows
- Event Graphics
- Promotions
- Exterior Applications up to 1 Year

# panoRama One8020, 7030, 6040, 5050

## MATERIAL

|                  |   |
|------------------|---|
| Face Film        | Printable White Perforated PVC              |
| Back Side        | Black for Maximum Contrast                  |
| Adhesive         | Removable Semi-Permanent Clear              |
| Liner            | Universal Paper Liner – 6 mil (150µ +/-10µ) |
| Film Thickness   | 5.7 mil (145µ +/-10µ)                       |
| Hole Diameter    | 1.5 mm                                      |
| FR Certification | ASTM E84                                    |

## DURABILITY

|                      |   |
|----------------------|---|
| Interior             | Up to 3 Years   |
| Exterior             | Up To 1 year - Vertical Exposure Under Normal Conditions                        |
| Environment          | Humidity & Solvent Resistance – Good  |
| Shelf Life           | 1 Year  |
| Storage Requirements | Store at 59°F to 68°F (+15°C to +20°C) and Relative Humidity between 45% to 65% |
| Repositionable       | No  |

## APPLICATION/REMOVAL

|                  |  |
|------------------|--|
| Application Temp | +50°F to +86°F (+10°C to +30°C)  |
| Service Temp     | +0°F to +122°F (-17°C to +50°C)  |
| Removability     | Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time     |
| Removal Temp     | +50°F (+10°C) or Greater   |
| Exclusions       | NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available) |

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean installation surface with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application. For full installation and removal recommendations, please refer to "panoRama Exterior Mount Perforated Window Film Application & Removal Guide."

\*For critical substrates and all surfaces, please test PRIOR to application.



## Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex



## Material Sizes

- 8020**
  - 54" x 50'
  - 54" x 164'
  - 54" x 656'
  - 60" x 50'
  - 60" x 164'
  - 60" x 656'
- 7030**
  - 54" x 164'
  - 54" x 656'
- 6040**
  - 54" x 164'
  - 54" x 656'
  - 60" x 164'
  - 60" x 656'
- 5050**
  - 54" x 164'



## Advantages

- Economical Perforated Window Film for Short-Term Applications
- Universal Liner for All Printing Methods
- Clean Removability (Up to 6 Months without Residue)
- Laminate with panoRama Cast or panoRama Protect for Maximum Protection and Durability

## → For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

**1-704-872-2216 • www.cgxusa.com**