



FLOOR GRAPHICS SYSTEM

WALK-ON GRAPHICS®

SPMWOG 4.0 mil. Matte White or Clear Flexible Vinyl - Base Film
6.0 mil. Clear Embossed Rigid Vinyl - Overlamine

Catalina Graphic Films' Mojave Digital Media family of Floor Graphics include Walk-On Graphics floor decal system consist of a two component, UL-approved system with a base film and a slip-resistant overlamine.

RECOMMENDED APPLICATIONS	BASE FILM OVERVIEW	OVERLAMINATE OVERVIEW
<ul style="list-style-type: none"> Floor Indoor 	Face Film WOGFW 3.5 mil matte white calendered PVC WOGFC 3.5 mil gloss clear calendered PVC Adhesive R32 clear removable adhesive Liner 90# Layflat liner Opacity WOGFW Good WOGFC Clear Gloss Level WOGFW Matte WOGFC Gloss Indoor Durability Up to 6 Months	Face Film 6.0 mil. Clear Embossed Rigid Vinyl Adhesive Permanent Acrylic Liner Clear Film Opacity Embossed Gloss Level Matte Indoor Durability Up to 6 Months

SPECIFICATIONS	
Application	Interior floor graphics applied to smooth flooring only. Application to textured and/or unfinished floor surfaces is not recommended.
Walk On Floor System Slip Resistant UL-Rating	The base film components WOGFW and WOGFC, along with the Clear Embossed Rigid Vinyl overlamine have all been tested as a system and are certified as compliant with UL 410 ("Slip Resistance of Floor Surface Materials") and are listed in UL file IMET.SA11746
Print Methods	Screen print, solvent and UV flat bed ink jet, & offset. Offset material requires a top coat
Minimum Surface / Ambient Air Application Temperature	+50° F. For lower application temperature requirements, ask your Catalina representative about our other adhesive recommendations
Service Temperature Range	+50° F to +150° F
Total Product Thickness	10.0 ± 1.0 mils – Base film + Overlamine
Solvent Resistance	Good for most petroleum based solvents. Edge sealing is recommended in high solvent exposure areas
Water Resistance	Excellent: test piece aged 24 hrs. applied to stainless steel is not affected when immersed in 70°F water for seven days
Adhesion	25 ± 2oz/in. (180° adhesion from SS, 24 hour room temperature dwell)
Base Film & Overlamine Shelf Life	One (1) year when stored under conditions of 70° F and 50% relative humidity
Indemnity	The use of both the Catalina Walk-On Graphics base films and the Catalina Walk-On Graphics overlamines are required for indemnification. Exchanging other base films or overlamines will not carry an indemnity policy.

The above information on physical and chemical characteristics is based upon tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. The purchaser should independently determine, prior to use, the suitability of this material for his/her specific purpose. (Data represents averages and is not intended for use as a specification.)

To order or request product samples,
contact your local authorized dealer or call direct

Customer Service **800-333-3136** or visit our websites:



27001 Agoura Road Suite 100
Calabasas Hills California 91301
 Phone: (818) 880-8060
 Fax: (818) 880-1144
 Atlanta Sales: (800) 922-5880
 Chicago Sales: (800) 766-4939
 E-mail: info@catalinagraphicfilms.com

